



Gulf Coolant XLL

Superior Ready to use Coolant (Premixed with Water)

Product Description

Gulf Coolant XLL is an Extended Life concentrate based on Mono Ethylene Glycol (MEG) and specially designed corrosion inhibitors to provide protection against frost and corrosion. It is mixed with 50% of water for using as cooling and heat transfer fluid in internal combustion engines. It is free from potentially harmful additives such as nitrites, amines, borate and phosphates and hence it contributes to a safer environment. It is neutral towards gaskets, hoses and provides good resistance against foam.

Features & Benefits

- It is extended life coolant based on virtually non depleting synergistic combination of corrosion inhibitors.
- It is having high boiling point which decreases the risk of overheating of Antifreeze.
- It has as improved hard water stability as it does not contain silicates and other mineral salts.
- It is compatible with elastomers used by most of the European OEMs.
- It prevents formation of deposits and scale on the surfaces and also compatible with other MEG based antifreeze.
- It is suitable for mixed fleet

Applications

- It is recommended for use in cooling systems of all types of liquid cooled **hi-tech** automotive engines where such types of coolants are used. (Please refer OEM manual for recommended coolant)
- It is particularly recommended where high temperature aluminum protection is important.

Warning: Keep all antifreezes out of reach of children. Do not drink antifreeze. If swallowed, induce vomiting and immediately seek medical advice.

Suitable for Use Applications & Typical Properties:

Meets the following Specifications		
ASTM D3306, ASTM D 4656, AFNOR 15-601, SAE J1034, JASO M325/JIS K2234		X
Ford WSS-M97B44-D, Mercedes Benz MB 325.3, General Motors GM 6277M, MAN 324 Type SNF, VW TL 774F		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Density @ 15°C, Kg/l	D 1298	1.116
Equilibrium Boiling Point °C	D 1120	108
Freezing point °C (50 vol %)	D 1177	-40
Reserve Alkalinity	D 1121	3.0
pH value (50 vol %)	D 1287	8.6

July 2016

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com