



## Gulf Syntrac 4T Synthetic 4-Stroke Motorcycle Oil

### Product Description

**Gulf Syntrac 4T** series are synthetic, 4-stroke gasoline engine oil developed specifically to meet the special requirements of latest high performance 4-stroke motorcycles. It is blended from synthetic base stocks and specially selected additive technology to exceed the most demanding lubrication requirements of modern 4-stroke motorcycles and provides optimal friction performance. It provides excellent protection to engine, gearbox and wet clutch used in 4-stroke motorcycles and ensures highest degree of reliability even under severe operating conditions. This oil exceeds the specifications of API SL and JASO MA2 and the requirements of leading global 4-stroke motorcycle manufacturers.

### Features & Benefits

- Excellent anti-wear properties protect vital engine and gear components leading to reduced maintenance costs
- Optimal frictional properties eliminate clutch slippage leading to increased power/ fuel economy and improves drivability
- Special detergents/ dispersants used in this oil ensure cleaner pistons leading to faster heat dissipation and longer engine life
- Excellent shear stability maintains viscosity under high temperature-high shear environment and provides improved wear protection
- Outstanding low temperature properties enable easy starting at low ambient temperatures and ensure effective lubrication and wear protection at start up
- Effective rust and corrosion inhibition property ensures longer life of critical engine components

### Applications

- Recommended for advanced 4-stroke gasoline engines in high performance motorcycles of leading global manufacturers operating in wide range of ambient temperatures

### Specifications & Typical Properties

Meets the following Specifications		5W-40	10W-40
API SL, JASO MA2		X	X
Typical Properties			
Test Parameters	ASTM Method	Typical Values	
Viscosity @ 100 °C, cSt	D 445	14.0	14.4
Viscosity Index	D 2270	167	165
Flash Point, °C	D 92	220	236
Pour Point, °C	D 97	-45	-45
Density @ 15°C, Kg/l	D 1298	0.845	0.846

GOSCO – March 2019

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

[www.gulfoilltd.com](http://www.gulfoilltd.com)