



Gulf Syntrac 4T Superbike Synthetic 4-Stroke Motorcycle Oil

Product Description

Gulf Syntrac 4T Superbike are synthetic, 4-stroke gasoline engine oils developed specifically to meet the special requirements of latest high performance air cooled 4-stroke racing bikes with wet clutch system. These are blended from synthetic blend containing PAO and advanced additive technology to exceed the most demanding lubrication requirements of modern 4-stroke motorcycles. They provide excellent protection to engine; gearbox and wet clutch used in 4-stroke motorcycles and ensures highest degree of reliability even under severe operating conditions. These oils meet the specifications of API SM, and JASO MA2.

Features & Benefits

- Controlled frictional properties eliminate clutch slippage leading to increased power and improves drivability
- Excellent thermo-oxidative stability minimises deposits and controls oil thickening facilitating extended engine and oil life even at enhanced operating temperature
- Exceptional anti-wear properties protect vital engine and gear components under extreme riding conditions.
- Special detergents/ dispersants used in this oil ensure cleaner pistons leading to faster heat dissipation and longer engine life
- Excellent shear stability maintains viscosity under high temperature-high shear environment and provides improved wear protection
- Effective rust and corrosion inhibition property ensures longer life of critical engine components

Applications

- High performance racing bikes with wet clutch system requiring JASO MA2 type of oils in SAE 10W-50 or SAE 15W-50 viscosity grades
- Also recommended for advanced 4-stroke gasoline engines in high performance motorcycles of leading global manufacturers operating in wide range of ambient temperatures

Specifications & Typical Properties

Meets the following Specifications		10W-50	15W-50
API SM, ACEA A3/B4, JASO MA2		X	X
Typical Properties			
Test Parameters	ASTM Method	Typical Values	
Viscosity @ 100 °C, cSt	D 445	17.6	17.9
Viscosity Index	D 2270	163	160
Flash Point, °C	D 92	215	212
Pour Point, °C	D 97	-39	-39
Density @ 15°C, Kg/l	D 1298	0.857	0.860

March 2017

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com